



## Standard packaging profiles and accessories ALUMINUM SPACER H 65

Noale 05.12.22

### PROFILES by 4 - 5 and 6 meters

Product	Width in mm	Distance between glasses in mm	Bars' length in meters and filling quantity for packaging unit									
			Cardboard boxes			Stillages						
			4 meters	5 meters	6 meters	5 CN type*	6 CN type*	6 CZ type*	5 NM type*	6 NM type*	6 ZM type*	
						5 meters	6 meters	6 meters	5 meters	6 meters	6 meters	
<b>Aluminum Spacer H 65</b> Traditional low profile aluminium and bendable.  *Stillages marked <b>CN</b> and <b>CZ</b> have spacers packed with paper between the layers.  *Stillages marked <b>NM</b> and <b>ZM</b> have spacers packed into bundles of 17 bars each.  The cardboard boxes for 5 m profiles measure: 510 x 17 x 17(H) cm.  The cardboard boxes for 6 m profiles measure: 610 x 17 x 17(H) cm.	4.0	4.5	1,800									
	5.5	6	2,400	3,000	3,600	15,000	18,000	30,000				
	6.5	7	2,160	2,700	3,240	15,000	18,000	31,500				
	7.5	8	1,920	2,400	2,880	16,420	19,704	27,000				
	8.5	9	1,680	2,100	2,520	14,575	17,490	24,480				20,808
	9.5	10	1,440	1,800	2,160	12,985	15,582	22,032			13,056	20,808
	10.5	11	1,320	1,650	1,980	11,660	13,992	19,890			12,240	18,972
	11.5	12	1,200	1,500	1,800	10,600	12,720	18,054	9,180	11,016	17,136	
	12.5	13	1,120	1,400	1,680	9,805	11,766	16,524		10,200	16,524	
	13.5	14	1,040	1,300	1,560	9,010	10,812	15,900	8,160	9,792	15,912	
	14.5	15	960	1,200	1,440	8,480	10,176	14,964	7,480	8,976	14,076	
	15.5	16	880	1,100	1,320	7,950	9,540	14,256	7,140	8,568	14,076	
	16.5	17	840	1,050	1,260	7,000	8,400					
	17.5	18	800	1,000	1,200	6,890	8,268	12,402	6,460	7,752	12,240	
	18.5	19		900								
	19.5	20	720	900	1,080	6,360	7,632	11,130	5,780	6,936	11,016	
	20.5	21		800								
	21.5	22	640	800	960	5,565	6,678	9,486		5,712		
	23.5	24	528	660	792	5,035	6,042	8,568		5,304		
	25.4	25.9		660								
26.5	27	528	660	792		4,988	7,800					



## Standard packaging profiles and accessories ALUMINUM SPACER H 65

Noale 05.12.22

ACCESSORIES												
Product	Width in mm	Distance between glasses in mm	For closing the frames						For the insertion of gases into the cavities			
			Connectors		Corner Keys				Corner Keys		Linears	
			Steel	Plastic	Steel		Plastic		Plastic		Plastic	
			Standard	Standard	Standard 90°	Flexibles	Standard 90°	Flexibles	With and without hole	Plugs	Supports	Stoppers
<b>Accessories for Aluminum Spacer H 65</b> (Pieces for box)  Standard connectors in steel and plastic.  Standard and flexible corner keys in steel and plastic.  For gas filling: Corner keys with hole, Corner keys without hole, Plugs, Supports, Stoppers.	4.0	4.5	2,500					5,000				
	5.5	6	2,500		5,000	5,000		5,000	1,000	2,000		
	6.5	7	2,500					5,000				
	7.5	8	2,500	5,000	5,000	5,000		5,000	5,000	2,000		
	8.5	9	2,500		5,000	5,000		5,000	1,000	2,000		
	9.5	10	2,500	5,000	5,000	5,000		5,000	1,000	2,000		
	10.5	11	2,500					5,000		2,000		
	11.5	12	2,500	5,000	2,500	5,000		5,000	1,000	2,000		
	12.5	13	2,500					5,000		2,000		
	13.5	14	2,500	5,000	2,500	2,500		5,000	1,000	2,000		
	14.5	15	2,500	5,000	2,500	2,500		5,000	1,000	2,000	1,000	
	15.5	16	2,000	5,000	2,500	2,500		5,000	1,000	2,000		
	16.5	17	1,500					5,000				
	17.5	18	1,500	4,000	2,500	2,500		5,000	1,000	2,000		
	18.5	19	1,500									
	19.5	20	1,500	4,000	2,500	2,500		4,000	4,000	2,000		
	20.5	21	1,500					3,500				
	21.5	22	1,500		2,500	2,500		3,500		2,000		
	23.5	24	1,500	3,000	2,500	2,500		2,000		2,000		
	25.4	25.9						2,000				
26,5	27	1,500					2,000					